

#### NOTES:

1. The minimum width of a median cut-through and median perpendicular curb ramp shall be 5 ft.
2. Where in-line or offset perpendicular curb ramps are used within a median, the turning space shall have a minimum clear dimension of 4 ft x 5 ft.
3. Where a median cut through is used the running slope shall be 2.00% maximum.
4. Where median width is less than 6 ft, detectable warning surfaces shall not be placed.
5. The bottom edge of the median cut-through or median perpendicular curb ramp and the top of curb shall be flush with the edge of adjacent pavement gutter line.
6. Walkable Surface. The cross slope shall be 2.00% maximum.
7. See Standard Drawing E 604-SWCR-01 for cross slope exceptions.
8. See Standard Drawing E 604-SWCR-12, -13, and -14 for Detectable Warning Surface placement, configuration, and details.
9. See Standard Drawing E 604-CCSJ-01 for sidewalk expansion joint details.

#### LEGEND:


- Ramp
- Detectable Warning Surface
- Turning Space

INDIANA DEPARTMENT OF TRANSPORTATION

MEDIAN CUT-THROUGH AND  
MEDIAN PERPENDICULAR CURB RAMP  
TYPICAL PLACEMENT

SEPTEMBER 2016

STANDARD DRAWING NO. E 604-SWCR-11



/s/ Elizabeth W. Phillips	03/15/16
DESIGN STANDARDS ENGINEER	DATE
/s/ Mark A. Miller	03/18/16
CHIEF ENGINEER	DATE